

### STRENGTH YOU CAN TRUST



**WALK BEHIND** VIBRATORY ROLLER

fiv6500





**FEATURES** 

**KOHLER KD 441 ENGINE** 

**EASY TO OPERATE & TRANSPORT** 

**FULLY HYDROSTATIC** 

HIGHLY EFFICIENT & RELIABLE

PAN INDIA ON-SITE SUPPORT

SPECIALLY DESIGNED LED LIGHT FOR NIGHT OPERATION





#### Operating Data - fiV 6500 **Basic Weight** 780Kgs **Drum Width** 650mm **Centrifugal Force High** 24kN **Centrifugal Force Low** 14kN **Frequency Vibration** 64Hz **Amplitudedrum** 0.50/0.25 mm **Travel Speed -Maximum** 5.90 km/hr Gradability 38% 7.5 HP **Engine Capacity Operating Performance** 5.6 kW @2600 Rpm **Tank Capacity Fuel** 5 Ltr - Diesel **Tank Capacity Water** 35 Ltr Fuel Consumption 1/h Avg 1 Ltr 3.50 Km/hr **Travel Speed -Minimum**

## WALK BEHIND VIBRATORY ROLLER



#### **APPLICATION**

HILLY TERRAINS WITH SHARP BENDS CULVERTS EDGES OF HIGHWAYS PARKING LOTS GARDENING COMPACTION CANALS ROAD WIDENING WORKS PLAYGROUNDS GRANULAR AND ASPHALT PAVEMENTS INTERNAL ROADS IN HOUSING ON SOIL CONSTRUCTION & REPAIR OF ROADS PRIVATE ROADS EMBANKMENTS

### **Specification**

Model	fi FDC 1000	fi FDC 1200	fi FDC 2000
Height(mm)	950	1130	1150
Drum Length (mm)	1000	1200	2000
Drum Dia (mm)	655	800	800
Weight (KG)	750	1150	1900
Centrifugal Force (Kn)	50	60	70
Working Flow ( L/Min)	50 - 80	55 - 85	55 - 85
Area covered for one Revaluation (Sqft/REV)	23	32	50
Nominal Amplitude (mm)	0.4	0.5	0.6
Vibrations (vib. / Min.)	1300	1800	2000

# SLOPE DRUM COMPACTOR



#### **APPLICATION**

IRRIGATION CANALS ROAD RAILWAYS TRENCH COMPACTION EMBANKMENTS WATER SEWAGE





Fine Centre, Behind Shroff's Srushti, Off Mumbai - Bangalore Highway, Mhalunge, Pune 411045. INDIA. Web: www.fineequipmet.net Mob: +91 83082 88600 Mob: +91 93264 39921 Email: info@fineequipment.net

